

Ejector Pin, Cylindrical Head
The hardened KSP
DIN ISO 1.7176

پران سراسطوانه

L \ D	100 mm	125 mm	160 mm	200 mm	250 mm	315 mm	360 mm	400 mm	450 mm	500 mm	550 mm	630 mm
3	140,000	180,000	210,000	290,000	350,000	430,000	640,000	770,000	-	-	-	-
4	180,000	210,000	240,000	320,000	380,000	460,000	700,000	830,000	970,000	1,150,000	-	-
5	190,000	210,000	270,000	350,000	420,000	540,000	770,000	940,000	1,080,000	1,240,000	-	-
6	210,000	240,000	300,000	380,000	540,000	650,000	890,000	1,030,000	1,240,000	1,400,000	1,610,000	1,940,000
8	240,000	300,000	400,000	560,000	650,000	800,000	1,180,000	1,400,000	1,670,000	1,910,000	2,160,000	2,580,000
10	400,000	480,000	610,000	780,000	940,000	1,210,000	1,750,000	2,040,000	2,460,000	2,810,000	3,230,000	3,820,000
12	600,000	740,000	880,000	1,050,000	1,270,000	1,590,000	2,470,000	2,770,000	3,260,000	3,810,000	4,260,000	5,190,000
14	740,000	810,000	1,050,000	1,290,000	1,530,000	1,910,000	2,810,000	3,290,000	3,810,000	4,430,000	5,190,000	6,020,000
16	880,000	980,000	1,260,000	1,500,000	1,880,000	2,400,000	3,430,000	4,020,000	4,880,000	5,340,000	6,090,000	7,200,000
18	980,000	1,150,000	1,470,000	1,770,000	2,220,000	2,840,000	3,920,000	4,630,000	5,810,000	6,540,000	7,200,000	8,470,000
20	1,180,000	1,420,000	1,770,000	2,190,000	2,770,000	3,290,000	5,190,000	5,850,000	6,910,000	7,890,000	9,540,000	10,750,000
22	1,770,000	2,080,000	2,700,000	3,530,000	4,290,000	5,190,000	7,920,000	9,060,000	10,780,000	12,580,000	14,580,000	17,270,000
25	2,500,000	2,940,000	3,600,000	5,120,000	6,300,000	7,440,000	11,480,000	13,410,000	15,720,000	17,900,000	20,660,000	24,700,000

